



Outdoor panel

ML-15HD

The ML-15HD is a unique outdoor panel for one subscriber, equipped with a built-in 2 MP camera with a color CMOS matrix, supporting AHD format that provides high-quality video signal and image transmission with no delay.

CAMERA RESOLUTION	2MP / 1MP / 960TVL	POWER	12 V from the indoor monitor
TYPE OF SIGNAL	AHD or CVBS (PAL)	CONSUMPTION	Up to 2.5 W
NIGHT BACKLIGHT	IR LED, up to 1.5 m	LOCK TYPE	Mechanical, up to 1 A current
SENSOR TYPE	1/2.9" CMOS	CALL BUTTON	Mechanical with backlight
VIEWING ANGLE	76°	INSTALLATION TYPE	Surface mount
MIN. ILLUMINATION	0,01 Lux	COLORS	Black, grey
BODY STRUCTURE	Metal alloy	TEMPERATURE RANGE	-40 ... +50 °C
PROTECTION CLASS	IP65	ADDITIONAL FUNCTIONS	Mechanical IR-cut filter
DIMENSIONS	49×128×41 mm		

Unique features



Operating temperature
-40 – +50 °C



Pinhole camera
Vandalproof camera protected from scratching



Viewing angle
76°



Camera mode switch
Switch the camera mode between AHD and CVBS



Product page