

SLINEX

Design. Uniqueness. Innovations



Outdoor panel

ML-17HD

The ML-17HD outdoor panel can be installed on the gates of residential complexes, at the entrance to the office, at gas stations, pharmacies, warehouses and other places where a secure entrance is required for a large number of people.

CAMERA RESOLUTION	2MP / 1MP / 960TVL	POWER	12 V from the monitor
TYPE OF SIGNAL	AHD or CVBS (PAL)	CONSUMPTION	Up to 3 W
NIGHT BACKLIGHT	IR LED, up to 1.5 m	LOCK TYPE	Mechanical or magnetic
SENSOR TYPE	1/2.9" CMOS	LOCK RELAY CURRENT	Up to 6 A
VIEWING ANGLE	130°	INSTALLATION TYPE	Surface mount with angle bracket (in the kit)
MIN. ILLUMINATION	0,01 Lux	COLORS	Black or silver
BODY STRUCTURE	Metal alloy	TEMPERATURE RANGE	-40 ... +50 °C
PROTECTION CLASS	IP65	ADDITIONAL FUNCTIONS	Mechanical IR-cut filter
DIMENSIONS	48×133×21 mm		

Unique features



Operating temperature
-40 – +50 °C



Call button backlight
LED button backlight in standby mode



Viewing angle
130°



Camera mode switch
Switch the camera mode between AHD and CVBS



Product page