

Design. Uniqueness. Innovations



## **ML-20CRHD**

The ML-20CRHD is equipped with an EM-Marin proximity card reader. The panel can store up to 248 unique identifiers inside its secure memory, which allows you to provide access to the premises to everyone you consider necessary.

**CAMERA RESOLUTION** 2MP/1MP/960TVL

**TYPE OF SIGNAL** AHD or CVBS (PAL)

**NIGHT BACKLIGHT** IR LED, up to 1.5 m

SENSOR TYPE 1/2.9" CMOS

VIEWING ANGLE 115°

MIN. ILLUMINATION 0.01 Lux

**BODY STRUCTURE** Metal alloy + acrylic glass

**PROTECTION CLASS** IP65

**DIMENSIONS** 45×130×24 mm

**POWER** 12 V from external power supply

**CONSUMPTION** Up to 2.5 W

**LOCK TYPE** Mechanical, up to 1 A current

**CALL BUTTON** Sensor, with backlight

**COLORS** Silver+black, gold+black

**ACCESS CONTROL** EM-Marin ID keys (248 pcs.)

**INSTALLATION TYPE** Surface or flush mount

**TEMPERATURE RANGE** -40 ... +50 °C

ADDITIONAL FUNCTIONS Mechanical IR-cut filter

## **Unique features**



Access control
Use EM-Marin wireless
cards to unlock the door



Call button backlight LED button backlight in standby mode





Camera mode switch Switch the camera mode between AHD and CVBS



Product page