



Outdoor panel

ML-40ID

ML-40ID outdoor panel provides convenient premises access for a large number of people. Assign up to 90 unique code combinations, Mifare IC cards or fingerprints to the panel's internal memory. Thus, immediately 90 people will be able to open the door using wireless cards, codes or fingerprints. More of it panel has AHD high resolution camera that provides detailed and nice image in any conditions.

VIDEO SIGNAL TYPE	AHD 1080p (2 Mp), AHD 720p (1 Mp) or CVBS	POWER	12 V from power supply
CAMERA SENSOR	1/3" CMOS, 1920×1080 pixels	CONSUMPTION	Up to 3 W in working mode
NIGHT BACKLIGHT	IR LED, up to 1.5 m	LOCK TYPE	Mechanical or magnetic, up to 2 A current
VIEWING ANGLE	120°	BUTTONS	Sensor, with backlight
MIN. ILLUMINATION	0,01 Lux	COLOR	Black+silver
BODY STRUCTURE	Plastic + acrylic glass	TEMPERATURE RANGE	−40 ... +50 °C
PROTECTION CLASS	IP65	ACCESS CONTROL	Mifare IC keys, user codes or fingerprints (up to 90 pcs.)
DIMENSIONS	53×143×27 mm (without rainshield)	ADDITIONAL FUNCTIONS	Mechanical IR-cut filter
INSTALLATION TYPE	Surface mount		

Unique features



Access control
Use Mifare wireless cards or key code to unlock the door



Buttons backlight
LED button backlight in working mode



Viewing angle
120°



Fingerprint sensor
Use personal biometry to unlock the door



Product page